

T: 905.563.4133 www.pllight.com





FIXTURE	HSE NXT-LP
Project	
Notes	




<b>208∨</b> 5.10A	<b>240∨</b> 4.42A	<b>277∨</b> 3.77A	347V 3.01A
5.10A	4.42A	3.77A	3.01 A
50/60Hz			
50/60Hz			
I,060₩	1,060W	1,045W	1,045W
HPS 1000W 400V Electronic			
	,	50/6 1,060W 1,060W	50/60Hz 1,060W 1,060W 1,045W


TECHNICAL SPECIFICATIONS <sup>†</sup> 600W						
RATED MAIN VOLTAGE	277V	347V				
Input Current	2.29A	1.84A				
Power Factor	>0.98					
Input Frequency	50/60Hz					
Actual Input Power 630W		W				
Lamp Type	HPS 600W 400V Electronic					
<sup>†</sup> Accurate to ± 10%						





Track/Truss Bracket – End View





Chain Mount Bracket – Front View

DIMENSIONS				
x = length	21.50 in. (54.61 cm)			
y = width	I I.00 in. (27.94 cm)			
z = height	7.50 in. (19.05 cm)			
weight	10.00 lb. (4.54 kg)			

 $\wedge$ 

For maximum lifetime and performance of the HPS ballast and lamp, do not rapidly cycle luminaire on and off. Always observe 15-30 minute wait time when luminaire is turned off before applying power again (restrike) to allow lamp to cool sufficiently. The control system should be limited to 2 power-up (strikes) / day. Excessive strikes / day may decrease the life of the ballast and/or lamp.

SPECIFICATION									
I. FIXTURE	2. FIXTURE WATTAGE	3. VOLTAGE	4. LIGHT SOURCE	5. REFLECTOR	6. CORD / PLUG	7. MOUNTING			
NXT-LP RST	600 Watts <sup>†</sup> 1000 Watts	208V* 240V* 277V 347V	600W USHIO HPS DBL 1000W PL Light HPS DBL 1000W Philips HPS DBL	Beta	Consult Factory	NXT-LP 2" x 1" Truss Bracket NXT-LP 1-5/8" Track Bracket			
	<sup>†</sup> special order only	*1000W only							

Warranty Terms: Fixtures warrantied for forty (40) months; electronic drivers forty (40) months; HPS Lamps four (4) years or 10,000 burning hours, whichever comes first. Complete system forty (40) month warranty period applies to product configurations with factory standard PL. Light Systems' ballast ONLY. Warranty period may vary for configurations with ballast and/or lamp by other manufacturers.

Due to continuous product improvements, specifications and dimensions are subject to change without notice. Certain options have limited compatibility with some other product selections. Consult www.pllight.com for most current technical information.