




P.L. LIGHT SYSTEMS

THE LIGHTING KNOWLEDGE COMPANY

T: 905.563.4133

www.pllight.com



PRODUCT	ParFX™ Ultra Max (3-Channel)
Project	
Notes	



TECHNICAL SPECIFICATIONS[†]

Rated Main Voltage		277-400V		
Amperage (max)		277V	347V	400V
	CHANNEL 1	4.3	3.5	3.0
	CHANNEL 2	0.5	0.4	0.3
	CHANNEL 3	0.7	0.6	0.5
Power	CHANNEL 1	1200W		
	CHANNEL 2	130W		
	CHANNEL 3	190W		
Light Source		LED		
Spectrum	CHANNEL 1	95% Red 5% Blue (4585 μmol/s @ 100%)		
	CHANNEL 2	Far-Red (365 μmol/s @ 100%)		
	CHANNEL 3	White (400 μmol/s @ 100%)		
Photon Flux (350-800nm)	Sample Recipe 1: R95:B5	Sample Recipe 2: R89:W5:B6	Sample Recipe 3: R81:W5:B6:FR8	
	4585 μmol/s	4345 μmol/s	4270 μmol/s	
Photon Efficacy (350-800nm)	Sample Recipe 1: R95:B5	Sample Recipe 2: R89:W5:B6	Sample Recipe 3: R81:W5:B6:FR8	
	3.82 μmol/J	3.62 μmol/J	3.56 μmol/J	
Power Factor		>0.97		
Input Frequency		50/60Hz		
Environment		35°C Max. Ambient Operating Temperature; Suitable for Wet Locations		
Lifetime (L90)		L90B5 at 50,000 hours*		

[†]Accurate to ± 10%

*Scientifically extrapolated calculation for Par Maintenance of light is L90B5 at 50,000hrs (this means that expected lifespan of LEDs is defined as ≤5% of luminaires can depreciate below the expected 90% PAR maintenance within 50,000 hours).

SPECIFICATION

1. LUMINAIRE	2. CHANNELS	3. COLOUR SPECTRUM	4. VOLTAGE	5. DIMMING
ParFX Ultra Max	3-Channel	Dynamic	277-400V	Digital Dim to Off* *Digital dimming is based on R5485 standard. Compatible with with HLP protocol module enabled climate control systems. Luminaire can be dimmed to 20% of max light output.


Limited warranty for a period of five (5) years, from date of invoice.




T: 905.563.4133
www.pllight.com

P.L. LIGHT SYSTEMS

THE LIGHTING KNOWLEDGE COMPANY




Medium Wide



Ultra-Wide

The ParFX Ultra Max lens, is optically engineered to deliver a medium- or ultra-wide batwing light distribution for exceptional uniformity. This ideal combination of wide light distribution and exceptionally high light output, enables wider spacing, so growers can achieve desired light levels—evenly across the surface of the crop—with fewer luminaires.



DIMENSIONS

Length (x)	27.87 in (708 mm)
Width (y)	15.16 in (385 mm)
Height (z)	4.13 in (105 mm)
Weight	35.3 lb. (16.0 kg)

